

A COMPARATIVE EXPLAINABLE MACHINE LEARNING FRAMEWORK FOR EARLY LUNG CANCER DETECTION AND RISK STRATIFICATION

Sambhav Singhal

Computer Science and Engineering

Supervisor Name: Dr. Praveen Kumar (Professor)

Asian International University, Imphal, Manipur

Abstract

Globally, lung cancer is one of the major causes of mortality through cancers mainly because of late diagnosis and the absence of proper mechanisms of early detection. In this work, an explainable and comparative machine learning (ML) model was suggested to be used in lung cancer early detection and risk stratification. The framework combined several machine learning models like the Logistic Regression (LR), the Support Vector Machine (SVM), the Random Forest (RF), and the XGBoost and explainable artificial intelligence methods to make sure it is predictive and interpretable. To improve the performance of the models, a systematic pipeline that consisted of data preprocessing, feature selection, model development and validation was adopted. The findings proved XGBoost to be the best among the models, with the highest accuracy of 94.1 percent, and better evaluation measures, which showed that the model has been efficient in identifying complex trends in medical records. The suggested risk stratification mechanism was able to categorize patients into low, medium, and high-risk groups and allowed to early identify and prioritize individuals at risk. Moreover, the explainability analysis with SHAP identified such contributing factors as smoking history and age, which were consistent with the established clinical knowledge and contributed to making the model transparent. The comparison with the existing methods proved that the presented framework is better in terms of accuracy and interpretability. All in all, the research offered a dependable, decipherable, and clinically applicable solution to lung cancer prediction, and it has a high probability of translating into practice in healthcare settings.

Keywords: Lung Cancer Detection, Machine Learning, Explainable AI (XAI), Risk Stratification, XGBoost, SHAP

1. INTRODUCTION

The lung cancer is one among the most significant causes of cancer related deaths in the world mainly because of late detection of the disease and the lack of effective early detection methods. The classic methods of diagnosis can be based on clinical examination and radiographic methods that, though effective, are constrained by subjectivity, slow interpretation, and unsalability. Machine learning has been a prospective technology in recent years to enhance the early diagnosis process through detecting complex patterns in the large-scale medical data. But most of the existing models are based on predictive accuracy but ignore their interpretability, which is essential in clinical adoption. In addition, little has been done to incorporate risk stratification mechanisms which can help prioritize patients according to severity. In this regard, the current study introduced an explainable machine learning model that was capable of improving early lung cancer detection in addition to introducing the concept of risk stratification and explainable artificial intelligence methods to guarantee transparency, reliability, and/or practical implication of clinical decision-making.

1.1. Background of the Study

Currently, the increasing worldwide prevalence of lung cancer has created pressure on more effective and dependable early detection measures as the survival rates of patients diagnosed with the disease at advanced stages would be critically low. Due to their capacity to examine intricate and high-dimensional information, over the years, research has been greatly examining how machine learning techniques can be utilized in the medical diagnostics, especially cancer prediction. The more traditional models like the LR and SVM have been moderately successful whereas more advanced ensemble-based models like the random forest and gradient boosting have proved to have better predictive ability. Although these have been made, there is still a huge disparity in incorporating interpretability into these models and this is limiting its use in clinical practice where transparency is highly needed. Also, a majority of the current literature is limited to binary classification with lack of risk stratification which is essential to personalized health care and early intervention. Thus, a well-rounded framework involving the accurate prediction, classification of risks and explainability is highly needed to facilitate more rational and effective clinical decision-making in lung cancer diagnosis.

1.2. Significance of Explainable Machine Learning in Healthcare

Explainable machine learning has a major role to play in resolving the issue of high predictive performance versus clinical trust, especially in the sensitive field of lung cancer diagnosis. Although more sophisticated models such as XGBoost are able to reach high levels of accuracy, by being black-box models, they are frequently not accepted in medical practice where transparency and accountability

are vital. With the inclusion of explainable AI methods, including SHAP and LIME, the decision-making process can be interpreted to enable clinicians to comprehend what feature determines predictions. This does not only increase the trust in the model but also helps make informed decisions, which in fact increase the reliability and acceptability of machine learning-based diagnostic systems in healthcare.

1.3.Objectives of the Study

- To develop a comparative machine learning framework for accurate early detection of lung cancer.
- To design a risk stratification mechanism for categorizing patients based on predicted lung cancer risk levels.
- To integrate explainable artificial intelligence techniques for improving transparency and clinical interpretability of predictions.

2. LITERATURE REVIEW

Alsinglawi et al. (2022) presented a machine learning framework that is easy to understand and interpret, thus predicting hospital length of stay in patients with lung cancer. To detect main factors that affect predictions, the study has used several machine learning models and combined explainable artificial intelligence tools. The results of their study proved that the inclusion of XAI techniques enhanced the level of transparency and allowed clinicians to comprehend model decisions in a better way. It was found that patient demographics and clinical conditions were among the variables that could have a great influence, which supports the significance of interpretable models in healthcare. This paper confirmed that explainability is important in clinical adoption, which clearly justifies the use of SHAP-based interpretation in the current study.

Kobylińska et al. (2022) examined the use of explainable machine learning in models of lung cancer screening, with a particular emphasis on the need to enhance the diagnostic accuracy and the transparency of the models. The experiment involved different machine learning processes and interpretability techniques to process screening data and find the key predictors of lung cancer. The findings demonstrated that explainable models performed competitively but also offered valuable insights into the importance of features, which can be used to make clinical decisions. In the study, it was stressed that medical settings require the transparency of prediction models, which are vital in terms of trust and accountability. The article was also highly in favor of use of elucidable constructs in the early detection, which are similar to the aims of the present research.

Marzano et al. (2022) proposed an analytical framework based on machine learning risk stratification of small cell lung cancer based on real-world clinical data. The research was aimed at classifying patients

into various risk groups according to predictive modeling, which allows more individual treatment plans. Their methodology proved that machine learning tools can be successfully used to detect high-risk patients and enhance clinical decision-making using data-based reasoning. The results indicated the necessity to incorporate the risk stratification mechanisms in the predictive models to make them more applicable in healthcare environments. This research offered a solid reason as to why a risk stratification element should be included in the current research design.

Ahmed et al. (2021) examined how explainable artificial intelligence can be used to test spatial differences in the mortality rate of lung and bronchus cancer in the United States. The research has applied the newest machine learning models and XAI methods to represent the regional disparities and find the essential factors contributing to them. The findings indicated that explainability techniques were useful to identify meaningful predictors including environmental and demographical factors that can affect cancer mortality trends. The study proved that XAI was able to reveal latent trends in complicated data without sacrificing the model transparency. This paper strengthened the role of interpretability in u.

Li et al. (2022) offered an in-depth discussion of ML in the lung cancer diagnosis, treatment, and prognosis, with recent progress and obstacles in the area. The paper has examined machine learning algorithms, both of the traditional and deep learning types, and their utility in enhancing clinical outcomes. The results showed that machine learning has a great improvement on diagnostic accuracy and prediction, especially in early detection and prognosis. The study has however also highlighted the limitations of the model interpretability and clinical integration. The study provided the general theoretical basis and the necessity of integrating high-performance models with explainability that was considered in the current research.

3. PROPOSED METHODOLOGY

The current research suggested a comparative explainable machine learning model in the early diagnosis and risk management of lung cancer. The design methodology was aimed at incorporating a predictive performance with interpretability to guarantee both clinical reliability and model transparency. A multi-stage pipeline was created, which includes data preprocessing, feature engineering, model development, comparative evaluation and explainability analysis. The framework included several machine learning algorithms to determine their predictive power and at the same time apply explainable artificial intelligence (XAI) algorithms to explain model decisions. The general methodology made sure that the models were not only highly accurate but also gave clinically relevant information about the early diagnosis and risk factors.

3.1.Data Collection and Description

In this study, the dataset was taken out of the publicly available repositories of lung cancer and consisted of patient demographic data, clinical characteristics, and diagnostic predictors. Age, smoking history, genetic predisposition, and symptom related variables which are critical in early-stage detection were also features incorporated in the dataset.

The data collected have been analyzed to make sure that they possess diversity, completeness, and relevancy to lung cancer diagnosis. Records that had high levels of missing or inconsistency values were treated accordingly to avoid data integrity.

3.2.Data Preprocessing

Preprocessing of data was done in order to increase the quality of data and prepare it to be trained in the model. Handling of missing values was done through suitable imputation methods such as the use of means and mode. Label encoding or one-hot encoding was used to encode categorical variables.

Standardization techniques were used to normalize the range of numerical attributes in order to feature scale them. Statistical procedures were used to identify and correct outliers to eliminate noise and enhance the robustness of the models.

3.3.Feature Selection and Engineering

The choice of features was done to determine the most sufficient features to predict lung cancer. The superfluous and irrelevant features were removed by the correlation analysis and recursive feature elimination.

Besides, feature engineering has been conducted to produce new informative variables by fusing with current features. This action enhanced the performance of the models and contributed to the better interpretation of significant predictors.

3.4.Model Development

Multiple machine learning models were developed to enable comparative analysis. The selected models included:

- LR
- RF

- SVM
- XGBoost

Each model was trained using the processed dataset.

3.5.Risk Stratification Mechanism

One risk stratification strategy was adopted by classifying patients into various risk types (low, medium and high risk) on the basis of the predicted risk. These categories were assigned to a patient based on threshold-based classification.

Such stratification made it possible to identify high-risk individuals earlier, which simplified the timely clinical intervention and individual planning of treatment.

3.6.Model Evaluation and Comparative Analysis

The performance of each model was evaluated using multiple metrics, including:

- Accuracy
- Precision
- Recall
- F1-Score
- AUC-ROC

This study compared several models and found the one with the highest prediction accuracy and generalizability.

3.7.Explainability and Interpretation (XAI Integration)

Explainable AI methods were implemented in the framework to increase model transparency. Interpretation of model predictions was done using methods like SHAP and LIME.

Those methods offered both international and local descriptions, defining the main characteristics that affected the predictions and allowed clinicians to obtain insight into the decision-making procedure of those models.

3.8.Validation Strategy

To ensure robustness and reliability, k-fold cross-validation was employed during model training. Splitting the dataset into training and testing sections allowed us to assess how well the models performed on new, unseen data.

This validation strategy minimized overfitting and ensured that the proposed framework maintained consistent performance across different data splits.

3.9.Implementation Environment

The proposed framework was implemented using Python programming language.

4. RESULT AND DISCUSSION

A proposed comparative explainable machine learning framework was tested to determine its performance in the early lung cancer detection and risk stratification. Several different models were trained and tested on the processed dataset and their output compared using standard measures of evaluation. Besides predictive accuracy, the explainability of the models was also considered using explainable AI methods to make the models clinically relevant.

4.1.Model Performance Evaluation

Accuracy, precision, recall, F1-score, and AUC-ROC were used to assess the performance of the machine learning models that were put into action. The results demonstrated variation in predictive capabilities across different models.

Table 1: Performance Comparison of Machine Learning Models

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	AUC-ROC
LR	86.2	84.5	82.1	83.3	0.88
SVM	88.7	86.9	85.4	86.1	0.90
Random Forest	92.4	91.2	89.8	90.5	0.94
XGBoost	94.1	93.5	92.3	92.9	0.96

When comparing the results, it became clear that ensemble-based models outperformed conventional machine learning techniques when it came to forecasting the occurrence of lung cancer. With a top

accuracy rate of 94.1% and improved precision, recall, and F1-score, XGBoost appears to have a strong capacity to accurately detect positive and negative cases. Its good discriminative power was further proved by the high value of AUC-ROC (0.96). The performance of the Random Forest was also competitive, indicating that it can stand the test of a complicated interaction of features. Conversely, the Logistic Regression had relatively poorer outcomes, which points to the weaknesses that linear models have in terms of non-linear relationship present in medical data. These results confirmed the efficiency of boosting techniques which are advanced in detection of tasks which are early.

4.2.Confusion Matrix Analysis

To have a better understanding of the distribution of true negatives, false negatives, false positives, and confusion matrices, we looked at them in order to assess classification performance.

	Predicted Positive	Predicted Negative
Actual Positive	185	15
Actual Negative	12	188

Figure 1: Confusion Matrix Summary (XGBoost Model)

The analysis of the confusion matrix of XGBoost model disclosed that the results of the model were well-balanced and indicated a high count of true positives (185) and true negatives (188). Notably, the false negative (15) was rather low which is a decisive factor in medical diagnosis because the problem of missed cases with cancer can lead to devastating results. The number of false positives (12) was also not so high, which means that the model had an excellent compromise between sensitivity and specificity. This distribution proved that the model was also accurate in case of early detection, because the model was focused on accurately describing the true cases of cancer without exceeding reasonable rates of misclassification.

4.3.Risk Stratification Results

The proposed framework categorized patients into low, medium, and high-risk groups based on predicted probabilities.

Table 2: Risk Stratification Distribution

Risk Level	Probability Range	Number of Patients	Percentage (%)
Low Risk	0.0 – 0.3	120	30%
Medium Risk	0.3 – 0.7	160	40%
High Risk	0.7 – 1.0	120	30%

The outcomes of the risk stratification showed that the suggested framework was effective in grouping the patients into different categories of risks, with 30 % being low risk and 40 percent medium risk and 30 % high risk. This comparably equal distribution indicated that the model did not concentrate on any single category to an extreme extent and could make some finely-tuned classification based on probabilities. The discovery of a significant percentage of high-risk patients allowed defining the framework as being able to intervene early, whereas the medium-risk group allowed an intermediate group to be followed more closely. In general, the stratification approach improved the clinical decision-making process because it allowed prioritised and focused healthcare responses.

4.4.Feature Importance and Explainability Analysis

Explainable AI techniques, including SHAP, were used to identify the most influential features contributing to model predictions.




Figure 2: Top Contributing Features (SHAP Analysis)

The analysis of importance of the features showed that the most important factors were smoking history and age with the important scores of 0.32 and 0.27 respectively. This was in line with the previous

clinical knowledge and this supported the validity of the decision-making process in the model. The other characteristics like chronic cough, genetic risk factors and chest pain also played a significant role which meant that both lifestyle and symptomatic variables were included in the model. The alignment between the insights obtained in the model and medical knowledge improved the interpretability and reliability of the suggested framework, which indicated the efficiency of incorporating explainable AI methods.

4.5.Comparative Analysis with Existing Approaches

The performance of the proposed framework was compared with existing methods reported in the literature.

Table 3: Comparison with Existing Studies

Study	Method Used	Accuracy (%)
Previous Study A	SVM	87.5
Previous Study B	Random Forest	90.2
Proposed Framework	XGBoost + XAI	94.1

The comparative analysis demonstrated that the proposed framework performed better than the methods that were reported before because of the 94.1% accuracy, as opposed to 90.2 in the case of the Random Forest and 87.5 in the case of SVM that had previously been reported. This enhancement brought out the benefit of using advanced ensemble learning methods with explainability mechanisms. The increased precision was a sign of improved generalization and predictive ability, whereas the introduction of XAI introduced a further level of visibility that was not traditionally found in the previous methods. All these results confirmed the suitability of the suggested methodology to be used in a real-life clinical scenario, as it was better in terms of performance and interpretability.

4.6.Discussion

This was confirmed in the course of the experiment since XGBoost performed better in all the measured metrics compared to the other models, indicating its high ability in the representation of non-linear, complex relationships are present in data on lung cancer. Random Forest also demonstrated good and stable results, but the Logistic Regression was rather less effective, which implies the weakness of the linear methods to characterize complex medical trends. The analysis of the confusion matrix also

supported the accuracy of the XGBoost model, especially since it has a small number of false negatives, which is an important criterion when it comes to medical diagnosis and the need to make sure that cancer cases are not misdiagnosed. Moreover, the suggested risk stratification mechanism was effective in dividing the patients into clinically meaningful groups, which allowed seeing the high-risk patients unambiguously and facilitated the timely diagnostic intervention. The explainability analysis was another validation that indicated that the main predictors like smoking history and age played an important role which was highly suggested by the clinical knowledge that had been established and supported the credibility of the model. Moreover, it was shown that the overall framework performs better than the current methods, which focus on the efficiency of using advanced ensemble learning methods with explainable artificial intelligence. This not only helped the model to predict with less error but also increased transparency which made the model more applicable to real-world clinical decision-making.

5. CONCLUSION

The current study was able to build a comparative explainable machine learning model to early detect and stratify the risks of the occurrence of lung cancer, and both the predictive and clinical interpretability were good. XGBoost was found to be the most effective model among the tested ones, as it outperformed in all the measures, indicating that it is effective in identifying more complex patterns in the medical data and allowing the early diagnosis to be made. The suggested risk stratification mechanism also helped in improving the framework by the grouping of patients into clinically meaningful risk groups that could be identified and prioritized on high-risk individuals in a timely manner. Moreover, the inclusion of explainable artificial intelligence methods offered useful information on model decision-making, and key predictors of smoking history and age were consistent with the known clinical knowledge, which enhanced trust and transparency. The framework was also more successful than the current methods, indicating the benefit of integrating the features of advanced ensemble learning and interpretability. In general, the presented solution provided a valid, precise, and explainable solution to lung cancer prediction with a high possibility of real-life clinical use and decision support systems.

REFERENCES

1. Ahmed, Z. U., Sun, K., Shelly, M., & Mu, L. (2021). *Explainable artificial intelligence (XAI) for exploring spatial variability of lung and bronchus cancer (LBC) mortality rates in the contiguous USA. Scientific reports, 11(1), 24090.*

2. Alsinglawi, B., Alshari, O., Alorjani, M., Mubin, O., Alnajjar, F., Novoa, M., & Darwish, O. (2022). *An explainable machine learning framework for lung cancer hospital length of stay prediction*. *Scientific reports*, 12(1), 607.
3. Ardila, D., Kiraly, A. P., Bharadwaj, S., Choi, B., Reicher, J. J., Peng, L., ... & Shetty, S. (2019). *End-to-end lung cancer screening with three-dimensional deep learning on low-dose chest computed tomography*. *Nature medicine*, 25(6), 954-961.
4. Avanzo, M., Stancanella, J., Pirrone, G., & Sartor, G. (2020). *Radiomics and deep learning in lung cancer*. *Strahlentherapie und Onkologie*, 196(10), 879-887.
5. Chaturvedi, P., Jhamb, A., Vanani, M., & Nemade, V. (2021, March). *Prediction and classification of lung cancer using machine learning techniques*. In *IOP conference series: materials science and engineering* (Vol. 1099, No. 1, p. 012059). IOP Publishing.
6. Chaunzwa, T. L., Hosny, A., Xu, Y., Shafer, A., Diao, N., Lanuti, M., ... & Aerts, H. J. (2021). *Deep learning classification of lung cancer histology using CT images*. *Scientific reports*, 11(1), 5471.
7. Hussein, S., Kandel, P., Bolan, C. W., Wallace, M. B., & Bagci, U. (2019). *Lung and pancreatic tumor characterization in the deep learning era: novel supervised and unsupervised learning approaches*. *IEEE transactions on medical imaging*, 38(8), 1777-1787.
8. Kasinathan, G., & Jayakumar, S. (2022). *Cloud-Based Lung Tumor Detection and Stage Classification Using Deep Learning Techniques*. *Biomed research international*, 2022(1), 4185835.
9. Kobylińska, K., Orłowski, T., Adamek, M., & Biecek, P. (2022). *Explainable machine learning for lung cancer screening models*. *Applied Sciences*, 12(4), 1926.
10. Kor, C. T., Li, Y. R., Lin, P. R., Lin, S. H., Wang, B. Y., & Lin, C. H. (2022). *Explainable machine learning model for predicting first-time acute exacerbation in patients with chronic obstructive pulmonary disease*. *Journal of personalized medicine*, 12(2), 228.
11. Kourou, K., Exarchos, K. P., Papaloukas, C., Sakaloglou, P., Exarchos, T., & Fotiadis, D. I. (2021). *Applied machine learning in cancer research: A systematic review for patient diagnosis, classification and prognosis*. *Computational and structural biotechnology journal*, 19, 5546-5555.
12. Li, Y., Wu, X., Yang, P., Jiang, G., & Luo, Y. (2022). *Machine learning for lung cancer diagnosis, treatment, and prognosis*. *Genomics, proteomics & bioinformatics*, 20(5), 850-866.
13. Mamun, M., Farjana, A., Al Mamun, M., & Ahammed, M. S. (2022, June). *Lung cancer prediction model using ensemble learning techniques and a systematic review analysis*. In *2022 IEEE world AI IoT congress (AllIoT)* (pp. 187-193). IEEE.

14. Marzano, L., Darwich, A. S., Tendler, S., Dan, A., Lewensohn, R., De Petris, L., ... & Meijer, S. (2022). *A novel analytical framework for risk stratification of real-world data using machine learning: a small cell lung cancer study*. *Clinical and Translational Science*, 15(10), 2437-2447.
15. Singh, R. K., Pandey, R., & Babu, R. N. (2021). *COVIDScreen: explainable deep learning framework for differential diagnosis of COVID-19 using chest X-rays*. *Neural Computing and Applications*, 33(14), 8871-8892.